

Metalion™ L

The 1st New-born Printable On-metal Label of Metalion™ Series



Metalion™ L, the new addition to Century RFID's Metalion™ Series, is an on-metal label with flexible design and suitable for flat or curved metal or other multi surfaces. Offered with preprint and encoding or blank to be printed and encoded on-demand using RFID enabled thermal transfer printers, the Metalion™ L is an excellent option for indoor applications that demand user flexibility and affordability.



KEY Features:

- Flexible design with strong adhesive for easy installation on flat or curved surfaces.
- Consistent and stable performance on and off metal.
- Durable materials, IP 67 rated Water-proof.
- Delivered in roll format, allows to be printed in batch on-demands, compatible with RFID enabled thermal transfer printers..
- Customized pre-printing artwork, barcode and QR code for easy deployment.

Application:

Metal shelving/racks, trollies/carts, metal bins, curved metal surfaces on tools, IT assets, appliances, machinery and other indoor assets that require on-demand generation of human readable labels in real-time and at point of application.






SPECIFICATIONS

Name	Metalion
Code No.	CE38004
PHYSICAL	
Dimension (mm/in)	97.5 X 27 X 0.9mm/(3.84" X1.06" X0.04")
Encasement	PET
Printing	Customized printing available
Mount way	Adhesive
Attachment on Curved Surface	Radius of curved surface ≥ 112 mm
ELECTRICAL	
Protocol	ISO/IEC 18000-6C & EPC global Class 1 Gen 2
Operating Frequency	902~928Mhz(US) 865~868Mhz(EU)
integrated Circuit [IC]	Impinj MR6 OR MR6-P
EPC Memory	96 bits
Unique TID	48 bits
Reading Distance	Read Range on Metal (EIRP 2W): 3 - 4 m (9.8 - 13.1 ft) Read Range off Metal (EIRP 2W): 4 - 5 m (13.0 - 16.4 ft)
Expected read cycles	100000 cycles
Data retention	10 years
PACKING	
Packing Format	Carton
Weight per pieces	1.6 g
Quantity per box	4000 pcs
Box Dimension	460 X 460 X140mm
Weight per box	6.5kg
Quality Assurance	100% performance tested
Average number of units per roll	1000 pcs
ENVIRONMENTAL	
Operating Temperature	-20°C ~ 60 °C
Operating Humidity	30 % ~ 70 %
Storage Temperature	-20°C ~ 60°C
Storage Humidity	30 % ~ 70 %
IP Rating	IP 67
Expected lifetime	10 years
Guarantee	2 years
Certificate	EPC Global

READ RANGE



For more information and free samples ,please contact your nearest Century RFID office

Century RFID Headquarters
528 Xingqi Road, Yuhang economic development Area, Hangzhou, PR, China
Email: rfid.info@century-cn.com Tel: +86-571-28818756

Century RFID America
10 N. Martingale Road, Suite 400, Schaumburg, IL 60173
Email: rfid.info@century-cn.com Tel: (877) 801-5087

www.centurylinkrfid.com
www.century-cn.com

This document and the information it contains are the exclusive property of Century RFID. All Rights reserved. Any unauthorized reproduction is strictly prohibited

